

## Test Report

No.: SHHL1807038192CE

Date: AUG. 01, 2018

Page: 1 of 12

CORRAVENI INDUSTRIES CO., LTD.

NO.3, LANE 1473, ZHENGUANG ROAD, SHANGHAI, CHINA

The following sample(s) was/were submitted and identified by the client as:

Sample Description : CLOSE-COUPLED CERAMIC TOILET, S-TRAP  
Style No. : PO121-S2  
Country of Origin : PRC  
Sample Receiving Date : JUL. 13, 2018  
Testing Period : JUL. 13, 2018 TO AUG. 01, 2018  
Testing Location : 3RD BUILDING, LANE 3999, XIUPU ROAD, PUDONG  
NEW AREA, SHANGHAI  
Test Performed : SELECTED TEST(S) AS REQUESTED BY APPLICANT  
Test Requested : 1. EN 997:2012+A1:2015 WC PANS AND WC SUITES  
WITH INTEGRAL TRAP (CLASS 1)  
2. EN 33:2011 WC PANS AND WC SUITES -  
CONNECTING DIMENSIONS  
Test Result(s) : FOR FURTHER DETAILS, PLEASE REFER TO THE  
FOLLOWING PAGE(S)  
Conclusion : THE SUBMITTED SAMPLE MET THE TEST  
REQUIREMENT.

\*\*\*\*\*

Signed for and on behalf of  
SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.



Yomoro Gu  
Authorized Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**  
4<sup>th</sup> Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 t (86) 400 960 9661 f (86-21) 6115 6899 www.sgsgroup.com.cn  
中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 t (86) 400 960 9661 f (86-21) 6115 6899 e sgs.china@sgs.com

■ **General product information**

**Manufactured from CORRAVENI INDUSTRIES CO., LTD.**

**THE SAMPLE SUBMITTED WAS A CLOSE COUPLED WC SUITES, MADE OF WHITE CERAMIC. WITH VERTICAL WASTE OUTLET, CLASS 1, FLUSH VOLUME: FULL FLUSH: 6L, REDUCED FLUSH: 3L.**

**Style No.: PO121-S2**

■ **Copy of marking plate and summary of test results (information/comments):**



CORRAVENI INDUSTRIES CO., LTD.  
 NO. 3, LANE 1473, ZHENGUANG ROAD, SHANGHAI, CHINA  
 18  
 Declaration of Performance DOP1807-PO121-S2  
 EN 997:2012+A1:2015-CL1 - 6A  
 Intended use: personal hygiene  
 Product type: WC pan and WC suite PO121-S2

Capacity of flushing water:	Pass
Backflow prevention (of foul air):	Pass
Cleanability:	Pass
Load resistance:	Pass
Valve reliability:	Pass
Water/leak tightness:	Pass
Durability:	Pass

**CE marking on the product**

■ **Summary of testing:**

**The submitted samples were tested and found to comply with applicable requirements of EN 997:2012+A1:2015 and EN 33:2011.**



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN\_Doccheck@sgs.com**  
 4<sup>th</sup> Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 t (86) 400 960 9661 f (86-21) 6115 6899 www.sgsgroup.com.cn  
 中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 t (86) 400 960 9661 f (86-21) 6115 6899 e sgs.china@sgs.com

**Test Conducted:**

**1. EN 997:2012+A1:2015 WC Pans and WC Suites with Integral Trap (Class 1)**

**2. EN 33:2011 WC pans and WC suites - Connecting dimensions**

Sample Size: 1 piece

Clause	Test Method/ Requirement	Result	Rating																																				
<b>1. EN 997:2012+A1:2015</b>																																							
5 Functional requirements and test methods for class 1 products																																							
5.1 Depth of Water Seal	When tested in accordance with 5.7.1, the depth of the water seal shall be not less than 50 mm.	Water Seal: 51mm	Pass																																				
5.2 Flushing requirements																																							
5.2.1 General	Table 1 correlates the flushing requirements to the WC pan type and flushing volume.  <table border="1" style="margin-left: auto; margin-right: auto;"> <caption>Table 1 — Flushing requirements</caption> <thead> <tr> <th>Type of WC pan in accordance with Table 2 and Table 3</th> <th>Wash of bowl (5.2.2)</th> <th>Flushing of toilet paper (5.2.3)</th> <th>Flushing of 50 plastic balls (5.2.4)</th> <th>Oversplashing (5.2.5)</th> <th>After-flush volume (5.2.6)</th> </tr> </thead> <tbody> <tr> <td>9</td> <td>X</td> <td>X</td> <td>X</td> <td>X</td> <td></td> </tr> <tr> <td>7</td> <td>X</td> <td>X</td> <td>X</td> <td>X</td> <td></td> </tr> <tr> <td>6</td> <td>X</td> <td>X</td> <td></td> <td>X</td> <td>X</td> </tr> <tr> <td>5</td> <td>X</td> <td>X</td> <td></td> <td>X</td> <td>X</td> </tr> <tr> <td>4</td> <td>X</td> <td>X</td> <td>X</td> <td>X</td> <td></td> </tr> </tbody> </table>	Type of WC pan in accordance with Table 2 and Table 3	Wash of bowl (5.2.2)	Flushing of toilet paper (5.2.3)	Flushing of 50 plastic balls (5.2.4)	Oversplashing (5.2.5)	After-flush volume (5.2.6)	9	X	X	X	X		7	X	X	X	X		6	X	X		X	X	5	X	X		X	X	4	X	X	X	X		Type of WC pan: 6	Pass
Type of WC pan in accordance with Table 2 and Table 3	Wash of bowl (5.2.2)	Flushing of toilet paper (5.2.3)	Flushing of 50 plastic balls (5.2.4)	Oversplashing (5.2.5)	After-flush volume (5.2.6)																																		
9	X	X	X	X																																			
7	X	X	X	X																																			
6	X	X		X	X																																		
5	X	X		X	X																																		
4	X	X	X	X																																			
5.2.2 Wash of Bowl	When tested in accordance with 5.7.2.3, the arithmetic average of any unflushed area below the rim and above the surface of the water in the trap shall not be more than 50 cm <sup>2</sup> after five flushing operations. In case of rimless WCs, the surface to be tested is the area between the water surface and a horizontal line 85 mm below the top edge of the bowl.	See Result 1	Pass																																				
5.2.3 Flushing of Toilet Paper	When tested in accordance with 5.7.2.4, 12 sheets of toilet paper shall be flushed out of the WC pan a minimum of 4 times out of five tests. For baby WC pans, 6 sheets of toilet paper shall be flushed out of the WC pan a minimum of 4 times out of five tests.	See Result 2	Pass																																				
5.2.4 Flushing of Fifty Small Plastic Balls	When tested in accordance with 5.7.2.5 after five tests, each with 50 balls, a minimum of 85% the balls shall be flushed out of the WC pan.	/	N/A																																				
5.2.5 Over-Splashing	When tested in accordance with 5.7.2.6, flushing water shall not splash beyond the rim of the bowl and wet the floor. Only a few small drops are permissible.	/	Pass																																				
5.2.6 After-flush Volume	When tested in accordance with 5.7.2.7, an after-flush volume of 2.5 L or 2.8 L as appropriate is required.	See Result 3	Pass																																				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**  
 4<sup>th</sup> Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233      t (86) 400 960 9661      f (86-21) 6115 6899      www.sgsgroup.com.cn  
 中国·上海·徐汇区宜山路889号4号楼 邮编: 200233      t (86) 400 960 9661      f (86-21) 6115 6899      e sgs.china@sgs.com

# Test Report

No.: SHHL1807038192CE

Date: AUG. 01, 2018

Page: 4 of 12

Clause	Test Method/ Requirement	Result	Rating
5.3 Water Absorption	When tested in accordance with 5.7.3, the arithmetic average for water absorption of glazed ceramic WC pans shall not exceed 0.5% by mass.	Water absorption: 0.3%	Pass
5.4 Static Load	When tested in accordance with 5.7.4, wall-hung and non-ceramic WC pans and suites shall withstand a force of 4.00 ± 0.05 kN without showing any evidence of cracking or permanent deformation. Experience has shown that pedestal ceramic WC pans and WC suites comply with this requirement.	/	Pass
5.5 Additional requirements of flushing cisterns for close-coupled suites and one-piece WCs			
5.5.1 General	If close-coupled suites and one-piece WCs comprising a flushing cistern and a WC pan supplied or specified by the manufacturer as a unit, the following requirements shall be fulfilled.	See Below	Pass
5.5.2 Inlet valve of the flushing cistern	Flushing cisterns shall have an inlet valve complying with EN 14124.	See Remark 1	Pass
5.5.3 Supply piping	All materials of the supply piping which could be in contact with drinking water shall not be danger to health. They shall not change the taste, aroma or visual appearance of the drinking water. The use of elastomeric flexible supply hoses complying with EN 13618 is permissible inside the assembly.	/	N/A
5.5.4 Flush volume(s) of the flushing cistern	The flush volume(s) for one-piece and close-coupled flushing cisterns supplied with a WC pan shall conform to the value(s) specified by the manufacturer according to Table 3, when measured as described in 5.7.5.1. Flushing cisterns or their components shall be marked to allow the correct volume(s) of flush to be achieved.	See Result 4	Pass
5.5.5 Leaktightness between flushing cistern and bowl	When tested in accordance with 5.7.5.2, there shall be no leakage between the WC pan and the flushing cistern.	/	Pass
5.5.6 Outlet valve leaktightness	When tested in accordance with 5.7.5.3, the outlet shall not show any leakage greater than three drops within 15 min.	/	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC (Shanghai) Technical Services Co., Ltd. 4<sup>th</sup> Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 t (86) 400 960 9661 f (86-21) 6115 6899 www.sgs.com.cn  
中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 t (86) 400 960 9661 f (86-21) 6115 6899 e [sgs.china@sgs.com](mailto:sgs.china@sgs.com)

Clause	Test Method/ Requirement	Result	Rating
5.5.7 Outlet valve reliability	When tested in accordance with 5.7.5.4, the outlet mechanism functions shall be ensured. The flushing device shall not show any failure or permanent distortion of any component including linkages that prevents normal operation of the mechanism. The outlet of the flushing device shall not show leakage greater than three drops within 15 min.	See Remark 2	Pass
5.5.8 Overflow	When tested as described in 5.7.5.5, the overflow shall meet the requirements specified below: a) The distance between the maximum water level and the overflow level shall be $\leq 20$ mm. b) The distance between the critical water level and the overflow level shall be $\leq 10$ mm. c) The distance between the meniscus level and the overflow level shall be $\leq 5$ mm.	a): 9mm b): 7mm c): 2mm	Pass
5.5.9 Safety margin – dimension “c”	When tested as described in 5.7.5.6, dimension “c” corresponding to the distance between the overflowing level and the maximum nominal water level indicated by the manufacturer shall be $\geq 20$ mm.	Dimension “c”: 36mm	Pass
5.5.10 Safety margin – dimension “a”	When tested as described in 5.7.5.7, the dimension “a” between the overflow level and the lowest point of the air inlet orifice of the inlet valve shall be 20 mm minimum as required in EN 1717, to prevent backflow. In the case of an adjustable overflow, the adjustment shall provide a dimension “a” of 20 mm minimum.	Dimension “a”: 22mm	Pass
5.6 Durability	Class 1 products conforming to the requirements of 5.2 to 5.4 and 5.5.5 to 5.5.10 are deemed to be durable.	/	Pass
<b>5.8 Types of independent WC pans, close-coupled suites and one-piece WCs</b>			
5.8.1 Nominal flush volume	Type and test volume for a full flush shall be defined by the manufacturer. Baby WC pans belong to type 5 or type 4. The nominal flush volume of independent WC pans shall correspond to one of the types given in Table2.	Close-coupled WC pan Claim: 6.0L/3.0L Actual: 6.0L/3.0L  See Result 4	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC (Shanghai) Technical Services Co., Ltd. 4<sup>th</sup> Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 t (86) 400 960 9661 f (86-21) 6115 6899 www.sgsgroup.com.cn  
 中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 t (86) 400 960 9661 f (86-21) 6115 6899 e sgs.china@sgs.com

Clause	Test Method/ Requirement	Result	Rating																																						
	<p style="text-align: center;"><b>Table 2 — Types of independent WC pans</b></p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Type</th> <th>Nominal flush volume  </th> <th>Test flush volume  </th> </tr> </thead> <tbody> <tr> <td>9</td> <td>9</td> <td>9<sup>0</sup><sub>-0,1</sub></td> </tr> <tr> <td>7</td> <td>7</td> <td>7<sup>0</sup><sub>-0,1</sub></td> </tr> <tr> <td>6</td> <td>6</td> <td>6<sup>0</sup><sub>-0,1</sub></td> </tr> <tr> <td>5</td> <td>5</td> <td>5<sup>0</sup><sub>-0,5</sub></td> </tr> <tr> <td>4</td> <td>4</td> <td>4<sup>0</sup><sub>-0,1</sub></td> </tr> </tbody> </table> <p>The nominal flush volume of close-coupled suites and one-piece WC pans shall correspond to one of the types given in Table 3.</p> <p style="text-align: center;"><b>Table 3 — Types of close-coupled suites and one-piece WC pans</b></p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Type</th> <th>Nominal flush volume  </th> <th>Test flush volume  </th> <th>Reduced flush volume  </th> </tr> </thead> <tbody> <tr> <td>9</td> <td>9</td> <td>9<sup>0</sup><sub>-1,4</sub></td> <td rowspan="5" style="vertical-align: middle;">Maximum 2/3 of the nominal flush volume as specified by the manufacturer</td> </tr> <tr> <td>7</td> <td>7</td> <td>7 ± 0,5</td> </tr> <tr> <td>6</td> <td>6</td> <td>6<sup>+0,4</sup><sub>-0,5</sub></td> </tr> <tr> <td>5</td> <td>5</td> <td>5<sup>+0,4</sup><sub>-0,5</sub></td> </tr> <tr> <td>4</td> <td>4</td> <td>4<sup>+1,0</sup><sub>-0,5</sub></td> </tr> </tbody> </table>	Type	Nominal flush volume 	Test flush volume 	9	9	9 <sup>0</sup> <sub>-0,1</sub>	7	7	7 <sup>0</sup> <sub>-0,1</sub>	6	6	6 <sup>0</sup> <sub>-0,1</sub>	5	5	5 <sup>0</sup> <sub>-0,5</sub>	4	4	4 <sup>0</sup> <sub>-0,1</sub>	Type	Nominal flush volume 	Test flush volume 	Reduced flush volume 	9	9	9 <sup>0</sup> <sub>-1,4</sub>	Maximum 2/3 of the nominal flush volume as specified by the manufacturer	7	7	7 ± 0,5	6	6	6 <sup>+0,4</sup> <sub>-0,5</sub>	5	5	5 <sup>+0,4</sup> <sub>-0,5</sub>	4	4	4 <sup>+1,0</sup> <sub>-0,5</sub>		
Type	Nominal flush volume 	Test flush volume 																																							
9	9	9 <sup>0</sup> <sub>-0,1</sub>																																							
7	7	7 <sup>0</sup> <sub>-0,1</sub>																																							
6	6	6 <sup>0</sup> <sub>-0,1</sub>																																							
5	5	5 <sup>0</sup> <sub>-0,5</sub>																																							
4	4	4 <sup>0</sup> <sub>-0,1</sub>																																							
Type	Nominal flush volume 	Test flush volume 	Reduced flush volume 																																						
9	9	9 <sup>0</sup> <sub>-1,4</sub>	Maximum 2/3 of the nominal flush volume as specified by the manufacturer																																						
7	7	7 ± 0,5																																							
6	6	6 <sup>+0,4</sup> <sub>-0,5</sub>																																							
5	5	5 <sup>+0,4</sup> <sub>-0,5</sub>																																							
4	4	4 <sup>+1,0</sup> <sub>-0,5</sub>																																							
5.8.2 Flushing devices	Independent WC pans shall be designed to be flushed by any one or both of the following separate flushing devices: Valve-type cistern Type A Pressure flush valve Type C	/	N/A																																						
5.8.3 Verification of types	1) Connect the flushing cistern to a water supply of (0.2±0.1) MPa and adjust the flush volume in accordance with the manufacturer's instructions. 2) Flush the flushing cistern 3 times and measure the flush volume to accuracy of ±0,1L. The water supply shall be closed during the flushing operation. 3) The WC pan shall be classified on the arithmetic average resulting from three flushing operations referring to Table 2 or Table 3. 4) The flushing tests in accordance with this standard shall be carried out on the basis of the WC pan type (see Table 1).	See Result 4	Pass																																						



# Test Report

No.: SHHL1807038192CE

Date: AUG. 01, 2018

Page: 7 of 12

Clause	Test Method/ Requirement	Result	Rating
7. Dangerous substances	National regulations on dangerous substances may require verification and declaration on release, and sometimes content, when construction products covered by this standard are placed on those markets. In the absence of European harmonized test methods, verification and declaration on release/content should be done taking into account national provisions in the place of use.	/	N/A
8. Marking	The intended use of close-coupled suites, one-piece and independent WC pans with integral trap is personal hygiene in accordance with the scope of this standard.  The intended use is also mentioned in Annex ZA, Tables ZA.1.1 and ZA.1.2. The abbreviation "PH" for the intended use personal hygiene may be used for CE-marking.  A schematic drawing of the product may optionally follow the abbreviation for personal hygiene.  Close-coupled suites, one-piece and independent WC pans with integral trap belong always to one class and type at least. For each class and type a set of requirements to be tested (see 9.2.2) is defined. Due to this a close-coupled suite, one-piece and independent WC pan with integral trap can be described with a designation code which includes all fulfilled essential requirements.  The relevant product characteristics and the Essential Characteristics for close-coupled suites, one-piece and independent WC pans with integral trap including their abbreviations are given in Tables 4 and 5.	CE label was provided	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**

SGS-CSTC Technical Services (Shanghai) Co., Ltd. 4<sup>th</sup> Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 t (86) 400 960 9661 f (86-21) 6115 6899 www.sgs.com.cn  
Testing Center Harbin 中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 t (86) 400 960 9661 f (86-21) 6115 6899 e sgs.china@sgs.com

Clause	Test Method/ Requirement	Result	Rating																																														
	<p style="text-align: center;">Table 4 — Characteristics and abbreviations for class 1 products</p> <table border="1"> <thead> <tr> <th>Abbreviation</th> <th>Characteristics</th> </tr> </thead> <tbody> <tr> <td>EN 997</td> <td>Number of European Standard for WCs and WC suites for product description</td> </tr> <tr> <td>CL 1 - X</td> <td>Class 1 product with fixed flush volumes (9 l, 7 l, 6 l, 5 l or 4 l)</td> </tr> <tr> <td>(Y)</td> <td>Minimum supply pressure (optionally)</td> </tr> <tr> <td>A</td> <td>Flushing cistern</td> </tr> <tr> <td>C</td> <td>Pressure flush valve</td> </tr> <tr> <td>WL</td> <td>Water tightness / leak tightness</td> </tr> <tr> <td>CF</td> <td>Capacity of flush</td> </tr> <tr> <td>BP</td> <td>Backflow prevention (foul air)</td> </tr> <tr> <td>CA</td> <td>Cleanability</td> </tr> <tr> <td>VR(x)</td> <td>Valve reliability (Class 1 close-coupled suites and one-piece WC pans only – category I or II)</td> </tr> <tr> <td>LR</td> <td>Load resistance</td> </tr> <tr> <td>DA</td> <td>Durability</td> </tr> </tbody> </table> <p style="text-align: center;">Table 5 — Characteristics and abbreviations for class 2 products</p> <table border="1"> <thead> <tr> <th>Abbreviation</th> <th>Characteristics</th> </tr> </thead> <tbody> <tr> <td>EN 997</td> <td>Number of European Standard for WCs and WC suites for product description</td> </tr> <tr> <td>CL 2 - Z</td> <td>Class 2 product with flush volume ≤ 6 l and optionally minimum full flush volume (as Z)</td> </tr> <tr> <td>WL</td> <td>Water tightness / leak tightness</td> </tr> <tr> <td>CF</td> <td>Capacity of flush</td> </tr> <tr> <td>BP</td> <td>Backflow prevention (foul air)</td> </tr> <tr> <td>VR</td> <td>Valve reliability</td> </tr> <tr> <td>CA</td> <td>Cleanability</td> </tr> <tr> <td>LR</td> <td>Load resistance</td> </tr> <tr> <td>DA</td> <td>Durability</td> </tr> </tbody> </table> <p>All close-coupled suites, one-piece and independent WC pans with integral trap shall be designated in accordance with the following system:</p> <p>Valve reliability (category I or II) _____</p> <p>Flushing device and optionally minimum supply pressure _____</p> <p>Minimum full flush volume, for class II optional _____</p> <p>Flush volume for class I _____</p> <p>Class of product _____</p> <p>Number of standard _____</p> <p style="text-align: center;">EN 997 — CL1 (or Z) — (X or Z) — A (or C) / Y — VR I (or II) WL — CF — BP — CA — VR — LR — DA</p> <p>Watertightness / leaktightness _____</p> <p>Capacity of flush _____</p> <p>Backflow prevention (of foul air) _____</p> <p>Cleanability _____</p> <p>Valve reliability _____</p> <p>Load resistance _____</p> <p>Durability _____</p> <p>The declaration of the characteristics of the second line is considered being covered by the declaration of the relevant class. However, the characteristics should be listed when one of</p>	Abbreviation	Characteristics	EN 997	Number of European Standard for WCs and WC suites for product description	CL 1 - X	Class 1 product with fixed flush volumes (9 l, 7 l, 6 l, 5 l or 4 l)	(Y)	Minimum supply pressure (optionally)	A	Flushing cistern	C	Pressure flush valve	WL	Water tightness / leak tightness	CF	Capacity of flush	BP	Backflow prevention (foul air)	CA	Cleanability	VR(x)	Valve reliability (Class 1 close-coupled suites and one-piece WC pans only – category I or II)	LR	Load resistance	DA	Durability	Abbreviation	Characteristics	EN 997	Number of European Standard for WCs and WC suites for product description	CL 2 - Z	Class 2 product with flush volume ≤ 6 l and optionally minimum full flush volume (as Z)	WL	Water tightness / leak tightness	CF	Capacity of flush	BP	Backflow prevention (foul air)	VR	Valve reliability	CA	Cleanability	LR	Load resistance	DA	Durability		
Abbreviation	Characteristics																																																
EN 997	Number of European Standard for WCs and WC suites for product description																																																
CL 1 - X	Class 1 product with fixed flush volumes (9 l, 7 l, 6 l, 5 l or 4 l)																																																
(Y)	Minimum supply pressure (optionally)																																																
A	Flushing cistern																																																
C	Pressure flush valve																																																
WL	Water tightness / leak tightness																																																
CF	Capacity of flush																																																
BP	Backflow prevention (foul air)																																																
CA	Cleanability																																																
VR(x)	Valve reliability (Class 1 close-coupled suites and one-piece WC pans only – category I or II)																																																
LR	Load resistance																																																
DA	Durability																																																
Abbreviation	Characteristics																																																
EN 997	Number of European Standard for WCs and WC suites for product description																																																
CL 2 - Z	Class 2 product with flush volume ≤ 6 l and optionally minimum full flush volume (as Z)																																																
WL	Water tightness / leak tightness																																																
CF	Capacity of flush																																																
BP	Backflow prevention (foul air)																																																
VR	Valve reliability																																																
CA	Cleanability																																																
LR	Load resistance																																																
DA	Durability																																																





Clause	Test Method/ Requirement	Result	Rating
	those characteristics is not declared.		
<b>2. EN 33:2011</b>			
2. Connecting dimensions			
2.1 Inlet of WC pans with independent water supply	The connecting dimensions of inlets of WC pans with independent water supply shall comply with the dimensions given in Tables 1, and 2.	/	N/A
2.2 Outlets of WC pans and WC suites	The connecting dimensions of WC pans outlets shall comply with the dimensions given in Tables 3 to 6.	See Result 5	Pass
3 Fixing dimensions for wall-hung WC pans and WC suites	The fixing dimensions for wall-hung WC pans and WC suites shall comply with the dimensions given in Table 7 and Figure 1.	/	N/A
4 Fixing dimensions for the seat	If the WC pan manufacturer does not provide a WC seat with the WC pan or does not recommend a suitable WC seat model, the fixing dimensions for the WC seat shall comply with the dimensions given in Table 8 and Figure 2. The angle is defined to ensure the stable position of the WC seat and its lid in the upright position (see Figures 3a to 3e).	See Result 6 See Remark 3	Pass

**Remark:**

1. The test report SHHL1805023412PL for inlet valve (side fill valve), issued by SGS lab on JUN. 08, 2018 was provided for test review.
2. The test report SHHL1611068947CE for outlet valve (flush valve), issued by SGS lab on Jan. 11, 2017 was provided for test review.
3. A suitable toilet seat was provided by client.
4. N/A = Not applicable.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. 4<sup>th</sup> Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 t (86) 400 960 9661 f (86-21) 6115 6899 www.sgsgroup.com.cn  
 中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 t (86) 400 960 9661 f (86-21) 6115 6899 e [sgs.china@sgs.com](mailto:sgs.china@sgs.com)

# Test Report

No.: SHHL1807038192CE

Date: AUG. 01, 2018

Page: 10 of 12

## Result 1 Wash of Bowl (cm<sup>2</sup>)

Flush times	1	2	3	4	5	Ave
Unflushed Area (Requirement: ≤50)	0	0	0	0	0	0

## Result 2 Flushing of Toilet Paper

Flush times	1	2	3	4	5
Number Flushed Out (Requirement: ≥4 times flushed out)	12	12	12	12	12

## Result 3 After-flush Volume (L)

Flush times	1	2	3	4	5	6	7	8	9	10	Ave
After-flush Volume (Requirement: minimum ≥2.5 average ≥2.8)	3.1	3.1	3.0	3.1	3.1	2.9	3.0	3.0	2.9	3.0	3.0

## Result 4 Flushing Volume of WC pans (L)

Flush times	1	2	3	Average
Full flush volume	6.0	6.0	6.0	6.0
Reduced flush volume	3.0	3.0	3.0	3.0



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. 4<sup>th</sup> Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 t (86) 400 960 9661 f (86-21) 6115 6899 www.sgsgroup.com.cn  
 中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 t (86) 400 960 9661 f (86-21) 6115 6899 e sgs.china@sgs.com

# Test Report

No.: SHHL1807038192CE

Date: AUG. 01, 2018

Page: 11 of 12

## Result 5 Outlets of WC pans and WC suites

### a) Outlet dimensions

Designation	Symbol	Requirement	Result(mm)
External diameter of the outlet	d5	102±5	99
External cylindrical part of the outlet without grooves	i	≥ 40	45
Diameter of the free space around the outlet	k	≥ 150	163
Distance between the centre line of the outlet and the base of the appliance	t1	180 <sup>+15</sup> <sub>-10</sub>	/
Distance from the plane passing through the end of the outlet and the base of the appliance	t2	≥ 10	15

### b) Pedestal WC suites

Designation	Symbol	Requirement	Result(mm)
Distance between the vertical plane passing through the end of the outlet and the part of the WC suite nearest to the wall	q <sub>1</sub>	140±25	/
	q <sub>2</sub>	100±25	/
Distance from the centre line of the outlet and the vertical plane passing through the part of the WC suite nearest to the wall	q <sub>3</sub>	≥ 115	/
		75±15	/
	q <sub>4</sub>	120±25	/
	q <sub>4</sub>	225±25	/
		120±25	/
		225±25	201

## Result 6 Fixing dimensions for the seat

Designation	Symbol	Requirement	Result(mm)
Diameter of holes	d <sub>6</sub>	15±2	14
Distance between the centres of holes	m	155±10	161
Distance between the centre line of holes and the front of the bowl	l	430±10	408
Angle between the vertical plane and the point P where an arc of length / taken from the centre line of the seat fixing holes meets the flushing cistern	α	≥ 8°	10°
Angle between the vertical plane and the point P where an arc of length / taken from the centre line of the seat fixing holes meets the wall			/



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC (Shanghai) Technical Services (Shanghai) Co., Ltd. 4<sup>th</sup> Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 t (86) 400 960 9661 f (86-21) 6115 6899 www.sgs.com.cn  
 中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 t (86) 400 960 9661 f (86-21) 6115 6899 e sgs.china@sgs.com

## Test Report

No.: SHHL1807038192CE

Date: AUG. 01, 2018

Page: 12 of 12

### Sample Photo:

Test sample (Front view)



Test sample (Side view)



Test sample (Top view)



Test sample (Flushing cistern)



SGS authenticate the photo on original report only

\*\*\*End of Report\*\*\*



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**  
 4<sup>th</sup> Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 t (86) 400 960 9661 f (86-21) 6115 6899 www.sgs.com.cn  
 中国·上海·徐汇区宜山路889号4号楼 邮编: 200233 t (86) 400 960 9661 f (86-21) 6115 6899 e sgs.china@sgs.com